TRANSPORT EMERGENCY CARD(ROAD)

CARGO WC 2000 Toilet bowl cleaner Honey coloured water thin liquid with a sharp odour.

NATURE OF HAZARD:

Corrosive. If inhaled, could be harmful. Fire could produce irritating or poisonous gases. Runoff from fire-control or dilution water could cause pollution. Incompatible with aluminium.

BASIC PERSONAL PROTECTION:

- Suitable respiratory protective device.
- Goggles giving complete protection to eyes. Eyewash bottle with clean water.
- Apron or other light protective clothing, boots and plastic or rubber gloves.

IMMEDIATE ACTION BY DRIVER - Notify police and fire brigade.

-If possible, move vehicle to open ground and stop engine.

No naked lights; No smoking; Mark roads and warn other road users.

-Keep public away from danger area; Keep upwind.

SPILLAGE:

Full protective clothing including breathing apparatus if spill is large and in a confined area.

Prevent entry into waterways, sewers, basements or confined areas.

PRECAUTIONS:

Restrict access to area.

Provide adequate protective equipment and ventilation.

Remove sources of heat and flame.

SPILL OR LEAK:

Shut off ignition sources; no smoking or flames in hazard area.

Stop leak if you can do it without risk.

SMALL SPILLS:

Takeup with sand or other noncombustible absorbent material and place into containers for later disposal.

LARGE SPILLS:

Dike far ahead of liquid spill for later disposal.

FIRE:

EXTINGUISHING MEDIA: N/A. Choose most appropriate for surrounding fire. UNUSUAL FIRE AND EXPLOSION HAZARDS: May produce irritating vapours. CONDITIONS OF FLAMMABILITY : N/A.

FIRST AID:

<u>Skin</u>	Wash affected area with plenty of soap and water for at least 20 minutes. SPEED IN REMOVING LIQUID FROM SKIN IS OF PRIME IMPORTANCE. Cover affected area with magnesia or baking soda. TO PREVENT, SERIOUS BURNS AND INJURY. Remove contaminated clothing immediately (flush clothes thoroughly with water after removing).
Eyes	Flush eyes with water for 15 minutes. Hold eyelids open while washing. Repeat irrigation if necessary. If pain persists, place 2-3 drops 1/2 % pontocaine solution in affected eye(s).
Ingested	Call doctor immediately. Drink a teaspoon or more of magnesia, or small pieces of soap softened with water.
Inhalation	If not breathing give artificial respiration. DO NOT USE MOUTH TO MOUTH METHOD IF

Inhalation VICTIM INGESTED OR INHALED THE SUBSTANCE. If breathing of victim is difficult administer oxygen for a maximum period of one hour.

Additional Information	Reinol-Janek Chemicals	Telephone	(011) 873-1826	
	<u>Un No 1789</u>	Hazchem Code	EAC	ERG No.

Reason for Alteration: General update: June 2022 (as per SABS 1344 & 1828 specification requirements.) Next scheduled update: June 2024 (as per SABS 1344 & 1828 specification requirements.) The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to the appropriate safety precautions.

TEC(R) - 50 Class: 8 Corrosive Group: II/III Subsidiary risk : None